



XT36

Doubling the performance of the most powerful 3-phase Quad microinverter

- Designed for 3-Phase grid connection
- 4 input channels
- Single unit connects to 8 modules
- Maximum continuous AC output power 3600VA
- Engineered to match the highest power modules available (Maximum input current 20A)
- Safety protection relay integrated
- Adjustable output power factor
- Balancing 3-phase output

PRODUCT FEATURES

XT36 is a native 3-phase microinverter capable of reaching unprecedented power outputs of 3600VA. Connecting up to 8 high power modules (4 by 2 in series), the XT36 provides a cost-efficient solution ideal for today's fast growing commercial PV segment.

The innovative design makes the product unique while maximizing power production. The components are encapsulated with silicone to reduce stress on electronics, facilitate thermal dissipation, enhance waterproof properties and ensure maximum reliability of the system via rigorous testing methods including accelerated life testing. 24/7 energy access through apps or web-based portal facilitate remote diagnosis and maintenance.

The new XT36 is interactive with power grids through a feature referred to as RPC (Reactive Power Control) to better manage photovoltaic power spikes in the grid. XT36 is a game changer in 3-phase installations for commercial PV rooftops capable of providing 97% of peak efficiency.

Input Data (DC)	
Recommended PV Module Power (STC) Range	315Wp-670Wp+
Peak Power Tracking Voltage	64V-90V
Operating Voltage Range	52V-118V
Maximum Input Voltage	118V
Maximum Input Current	20A x 4
Isc PV (absolute maximum)	25A x 4
Max. inverter backfeed current to the array	0A
Output Data (AC)	
Maximum Continuous Output Power	3600VA
Nominal Output Voltage/Range ⁽¹⁾	415V/ 352V-457V
Adjustable Output Voltage Range	352V-457V
Nominal Output Current	5.0A x 3
Nominal Output Frequency/ Range ⁽¹⁾	50Hz/47.5-52Hz
Adjustable Output Frequency Range	45Hz-55Hz
Power Factor Range	0.99 / 0.8 leading...0.8 lagging
Maximum Units per 4mm ² Branch ⁽²⁾	5
Maximum output fault current	16A
Maximum output overcurrent protection	6.3A
Protective class	I
Efficiency	
Peak Efficiency	97%
Nominal MPPT Efficiency	99.9%
Night Power Consumption	40mW
Mechanical Data	
Operating Ambient Temperature Range ⁽³⁾	-40 °C to +60 °C
Storage Temperature Range	-40 °C to +85 °C
Dimensions (W x H x D)	359 mm X 273 mm X 56 mm
Weight	7kg
AC Bus Cable	4mm ² (28A)
DC Connector Type	MC4 or MC4 Compatible
Cooling	Natural Convection - No Fans
Enclosure Environmental Rating	IP67
Features	
Communication (Inverter To ECU) ⁽⁴⁾	Encrypted ZigBee
Isolation Design	High Frequency Transformers, Galvanically Isolated
Energy Management	Via SILRES monitoring portal
Warranty ⁽⁵⁾	10 Years Standard; Extended Warranty Optional
Compliances	
Compliance	IS 16169/ IEC 62116, IS 16221 / IEC 62109 - 1, IEC 62109 - 2, IEC 61683:1999, IEC 60529, IEC 61000-3-2, 3-3, 3-11, 6-1, 6-3, IEC 60068-2-1, 2-2, 2-14, 2-30, 2-78

(1) Nominal Voltage/ Frequency range can be extended beyond nominal if required by the utility

(2) Limits may vary. Refer to local requirements to define the number of microinverters per branch in your area

(3) The inverter may enter power de-grade mode when the inverters are under poor ventilation and heat dissipation installation environment

(4) Recommend no more than 80 inverters register to one ECU for stable communication

(5) To be eligible for the warranty, SILRES microinverters need to be connected via SILRES monitoring portal

Please refer to our warranty T&Cs available on www.feniceenergy.com

Specifications subject to change without notice; please ensure you are using the most recent update found at web: www.feniceenergy.com

© All Rights Reserved

SILRES Energy Solutions Private Limited

30/5, 4, 1st cross street, R A Puram,

Govindaswamy Nagar, Chennai 600028.

+91-9500031672, inverter@silresenergy.com